

ISO 100

Bar and Chain Oil

Description

Wakefield Bar and Chain Oil ISO 100 is premium all weather oil providing anti-wear and corrosion protection. It contains ZDDP and over-based sulphonate additives along with anti-oxidants.

Advantages

- Suitable for all weather applications
- Superior Anti-Wear
- Better Corrosion Protection

Typical Characteristics

Name	Method	ISO 100
Appearance	Visual	Dark red/Clear
Viscosity @ 100° C, cSt	ASTM D-455	12.8
Viscosity @ 40° C, cSt	ASTM D-455	105.1
Viscosity Index	ASTM D-2270	116
Pour Point ° C	ASTM D-5949	-24
Calcium, ppm	ASTM D-5185	356
Phosphorus, ppm	ASTM D-5185	208
Zinc, ppm	ASTM D-5185	204
Rust and Corrosion Test	ASTM D-665	pass
Wear Test, 4 ball wear	ASTM D-4172	0.49 mm scar

Health and Safety

Based on available information, this product is not expected to produce adverse effect on health when used for the application referred to above and the recommendations provided in the Safety Data Sheet (SDS) are followed. SDS is available upon request through your sales contact office. This product should not be used for purposes other than the applications referred to above. If disposing off used product, take care to protect the environment, return used oil to collection centre.